

812070 - Subaru Front License Plate Delete WRX - STI



812070

COBB Tuning Subaru Front License Plate Delete WRX/STI 06-14



Congratulations on your purchase of the COBB Tuning Subaru Front License Plate Delete! The following instructions will assist you through your installation process. Please read them first BEFORE beginning the install and familiarize yourself with the steps and tools needed. If you feel that you cannot properly perform this installation, we HIGHLY recommend you take the vehicle to a qualified and experienced automotive technician.

Part List

- License Plate Delete
- (2) Plate Hook/Anchor
- (2) M5 x 12mm Screw

Tools Needed

- Phillips Screwdriver
-

Installation of COBB Subaru Front License Plate Delete

1. Locate the two mounting locations on the front of your bumper. Place the two hooks/anchors inside the holes and click into the outer edges of the holes.



2. Insert one of the provided screws through one of the holes on the license plate delete. Line this screw up with the corresponding anchor in the bumper cover and begin to tighten, leaving some slack. Repeat this process for the opposite side.



3. Tighten both screws until the license plate delete is tightly secured.

Congratulations on your new COBB License Plate Delete!

Links

[Subaru Installation Instructions](#)

Main Installation Instruction Repository for Subaru Parts

[SUBARU CALIBRATION SUPPORT](#)

Link to Subaru Map Notes to see what map you should be on given the parts you've added

Contact Us:

COBB Customer Support

Web Support and Tech Articles: [COBB Tuning Customer Support Center](#)

Email: support@cobbtuning.com

Phone support available 9am to 6pm Monday-Thursday. 9am to 4pm Friday (CST)

866.922.3059

return to www.cobbtuning.com