

VERUS ENGINEERING

ND Chassis Miata Rear Diffuser

Install Manual



Author: Eric Hazen

Release Date: 2016/09/23

Approvals: E. Hazen, P. Lucas

Document Revisions

Rev	Date	Author	Description
01	2016/09/23	E.Hazen	Initial release of install manual
02	2017/08/08	P. Lucas	Company name change from Velox to Verus

Confidential: Property of Verus Engineering. Not for Distribution outside intended recipient list.

CONTENTS

1. Introduction.....	<3>
1.1. Overview	<3>
1.2. Difficulty	<3>
1.3. Time Required	<3>
1.4. Tools Needed	<3>
1.5. Rear Diffuser Components	<3>
2. Front Splitter Install.....	<4-12>

ND Miata Rear Diffuser – Install Manual

1. Introduction

1.1. Overview: Detailed instructions on installing the ND Miata rear diffuser.

1.2. Difficulty: Beginner

1.3. Time Required: 1.5-2 hours

1.4. Tools Needed:

- 1.4.1. Jack
- 1.4.2. Jack Stands
- 1.4.3. Ratchet
- 1.4.4. 10mm socket
- 1.4.5. 12mm socket
- 1.4.6. Phillips screwdriver
- 1.4.7. 4mm allen wrench
- 1.4.8. 10mm wrench
- 1.4.9. Level

1.5. Rear Diffuser Components

- 1.5.1. (1) Rear Diffuser
- 1.5.2. (2) Front Brackets
- 1.5.3. (2) Rear Brackets
- 1.5.4. (1) Hardware Bag
 - 1.5.4.1. (13) M6 x 1.0 SS BHCS, 20mm Length
 - 1.5.4.2. (18) M6 SS Washers
 - 1.5.4.3. (13) M6 x 1.0 Flanged SS Serrated Nut
 - 1.5.4.4. (6) M6 x 1.0 SS BHCS, 35mm Length
 - 1.5.4.5. (6) 5mm Long Nylon Spacer
 - 1.5.4.6. (6) 10mm Long Nylon Spacer
 - 1.5.4.7. (6) 15mm Long Nylon Spacer



Confidential: Property of Verus Engineering. Not for Distribution outside intended recipient list.

ND Miata Rear Diffuser – Install Manual

2. Rear Diffuser Installation


- 2.1. Velox is not responsible for damage to you or your vehicle by following this manual and/or installing Verus Engineering products
- 2.2. We begin by jacking the car up. You'll want to choke the front wheels and do this on a flat surface to ensure the car does not want to roll away.
- 2.3. Place a jack stand on either side of the car, you can use the frame rails or the pinch welds.
- 2.4. With the rear of the car off the ground, we can get a better idea of what we're working with.
- 2.5. Starting with the rear sway bar mounting locations, fully remove the bottom nuts (circled in blue), and loosen the top nuts (circled in red) with the 12mm socket. There is a sway bar mount location on the left and the right, do this to both side. Shown below is the passenger side.



Confidential: Property of Verus Engineering. Not for Distribution outside intended recipient list.

ND Miata Rear Diffuser – Install Manual

- 2.6. Grab the small front brackets, and install these on each of the rear sway bar mounting locations as shown below. Note the orientation of the bracket.




- 2.7. Moving outward, remove the (2) Philips head screws which hold on the rear bumper. Both left and right side of the rear bumper needs these removed. The screw locations are circled in yellow below.



Confidential: Property of Verus Engineering. Not for Distribution outside intended recipient list.

ND Miata Rear Diffuser – Install Manual

2.8. With these bolts removed, you're left with the below image.



2.9. Reach up into the fender liner and remove the (2) plastic clips on each side of the rear bumper. These clips are shown below, removed.




2.10. Without these clips, the bumper has an open hole as shown below.

Confidential: Property of Verus Engineering. Not for Distribution outside intended recipient list.

ND Miata Rear Diffuser – Install Manual



- 2.11.** Moving rearward, we find the two rear most mounting points for the diffuser. These locations are circled in yellow below.




- 2.12.** Grab the long, rear mounting brackets. These install with larger angle attaching to the chassis and the sharper angle will bolt to the diffuser. Use an M6x1.0 x 20mm long bolt and

Confidential: Property of Verus Engineering. Not for Distribution outside intended recipient list.

ND Miata Rear Diffuser – Install Manual

stainless washer on the bracket, and a nut on top of the chassis location. Tighten this bracket fully.



- 2.13.** At this point, everything is ready for the diffuser to be installed. An extra set of hands is definitely helpful at this point in time.
- 2.14.** Mounting height of the diffuser is dependent on the exhaust. The spacers will come into play on the rear (6) mounting points, with no spacers being used for the furthest upward installed height.
- 2.15.** If you have the club sport aero rear lip, and the diffuser can be installed fully upward, you'll have to slide the side mounting points under the lips mounting as shown below. This must happen before any other mounting points are installed.




Confidential: Property of Verus Engineering. Not for Distribution outside intended recipient list.

ND Miata Rear Diffuser – Install Manual

- 2.16.** Starting with the front brackets, install (4) M6x1.0 x 20mm bolts with a washer on the front side of the diffuser. Place the nut on the bracket side (rear of diffuser) as shown below. Do not fully tighten these yet.



- 2.17.** Moving rearward, install the rear two locations. Install height will determine if you use the 20mm long M6x1.0 bolt or the 35mm long bolt. If the diffuser is installed low, longer bolts will be required with more spacers. If the diffuser is installed relatively high up, the shorter bolts can be used. Shown below we used the 5mm spacers.



Confidential: Property of Verus Engineering. Not for Distribution outside intended recipient list.

ND Miata Rear Diffuser – Install Manual

- 2.18.** Once again the button heads are on the bottom with a washer, and the nut goes on top.
- 2.19.** Finally, moving to the sides of the diffusers, install the button heads and washers on the bottom, and reaching up, into the fender, thread the nut on the top surface.




- 2.20.** At this point, the diffuser is completely mounted and all the bolts are snug but not fully tightened.
- 2.21.** With the car on level ground, take the level and take a look at lateral level (left to right) and ensure it is level. It should be as long as the spacers installed are the same throughout.
- 2.22.** Moving onto the crucial part of performance, ensure the forward most part of the diffuser (circled in yellow) is also level, longitudinally (forward to rear). This ensures the correct diffuser angles are achieved for maximum benefits.




Confidential: Property of Verus Engineering. Not for Distribution outside intended recipient list.

ND Miata Rear Diffuser – Install Manual

- 2.23. If everything is level as it should be, fully tighten all the bolts.
- 2.24. Tighten the front (4) M6 bolts (circled in red).




- 2.25. Tighten the front bracket to sway bar points which are 12mm hex head bolts to 16 ft-lbs (circled in blue).



Confidential: Property of Verus Engineering. Not for Distribution outside intended recipient list.

ND Miata Rear Diffuser – Install Manual

- 2.26.** Tighten the outside (4) mounting points with the 4mm allen wrench. The serrated nut should not need held as it will resist turning while you tighten the bolts.



- 2.27.** Finally, tighten the rear two M6 x 1.0 button heads with the proper spacer used.



- 2.28.** This concludes the ND Miata diffuser install. Please send any comments, concerns, questions, and general feedback to Verus Engineering via sales@verus-engineering.com.